



ClareOne Mini Door/Window Sensor

CLR-C1-MDW-W
CLR-C1-MDW-B

Intrusion



Specifications

Compatible panel	ClareOne (CLR-C1-PNL1)
Transmitter frequency	433MHz
Encrypted	Yes
Operating gap	0.8 in (20.3 mm)
Transmitted indications	Tamper and low battery
Supervisory keep-alive	60-70 minutes
Battery type	(2x) CR2032
Battery life	8 to 10 years
Operating temperature	32 to 120°F (0 to 49°C)
Relative humidity	95% non condensing
Dimensions (W x H x D)	1 x 2.25 x .5 in. (25.4 x 57.15x 12.7 mm)
Water resistant	No
Certifications	FCC: 15.109 Class B 15.231, Industry Canada: ICES-003, RSS-210

The ClareOne Mini Door/Window Sensor places intrusion alerts in all common entry points. This magnetic sensor's small form factor is designed to fit seamlessly alongside a door or window frame. When the door or window is opened, the magnetic contact is disrupted, and the sensor transmits an alarm notification to the ClareOne panel.

Performance Highlights:

- Small form factor design
- Available in white or brown
- Superior RF range and performance
- Can be mounted using supplied adhesive or screws
- Encrypted technology prevents alarm takeovers
- Pairs easily and quickly with the ClareOne panel

Options

ClareOne Door/Window Sensor, White	CLR-C1-MDW-W
ClareOne Door/Window Sensor, Brown	CLR-C1-MDW-B

By making home technology simple, Clare provides exclusive benefits to integrators, builders, and homeowners. We offer innovative home automation solutions, wireless security, controllable lighting, and IP CCTV components. For more information, visit clarecontrols.com.